



Hydraulic equipment



Dust control products



Safety Products



Please contact your dealer for more information:



Copyright 2017, Dehaco B.V.

Dehaco reserves the right to develop and alter products without further notice.
Misprints and printing errors reserved.
The colour of the products may vary slightly from those shown in this brochure.



EN/TeraDust control units110/230/2017-11



**Dust control units
110/230V series**



Dehaco Tera Dust Control Unit

In order to prevent dust from being released during demolition or renovation work, Dehaco expanded its range with a series of innovative Tera dust control units. These are widely applicable machines, as they can be used for both asbestos removal work (in containment) and small to medium-sized demolition and renovation projects.

Everything revolves around a targeted diffusion of fine water spray to which dust particles will attach. The revolutionary (patented) Demto-Rotor® spray head that is used starting from the Tera 15, does away with all the disadvantages that conventional nozzles have, such as clogging as a result of lime particles in the water.



INNOVATIE

ECO

Femto

The Femto is in its element with renovation works. Its small dimensions make it very portable. The Femto, with its very fine vaporisation, consumes very little water, so 'dry' working is possible.

The Femto is easy to move and has a water consumption of only 8 litres per hour.



FEMTO			
Weight	kg	5	
Range	m	0 - 10	
Electrical supply	V	230	110
Water consumption	ltr/h	0 - 20	
Water connection		Garden Hose Connector	
Water tank*	ltr	4	
Product code		4010.0005	4010.0006

Tera 15

The Tera 15 is the innovative successor of the De-Dust Nano and has been improved in many ways. For instance, the Tera 15 has been provided with a newly designed aluminium frame with two carrying handles. The centre of gravity has been adapted as well, making it even easier to move the Tera 15. A number of small technical changes have been made, reducing the water consumption to 40 litres per hour. A significant reduction compared to its predecessor that still used 90 litres of water per hour. The fan can be adjusted in three positions, i.e. ECO, ECO-Boost and PowerBoost.

TERA 15			
Weight	kg	21.4	
Range	m	0 - 15	
Electrical supply	V	230	110
Water consumption	ltr/h	0 - 40	
Water connection		Garden Hose Connector	
Product code		4010.0022	4010.0023



Tera 25

The Tera 25 is ideal for medium-sized demolition and renovation projects. The machine is easy to move and has a relatively large capacity. By using 230V and a Gardena® water connection, it can always be connected directly. The powerful Demto-Rotor® produces a good spray. The revolutionary (patented) Demto-Rotor® spray head that is used starting from the Tera 15, does away with all the disadvantages that conventional nozzles have, such as clogging as a result of lime particles in the water.

TERA 25			
Weight	kg	90	
Range	m	0 - 20	
Electrical supply	V	230	110
Water consumption	ltr/h	0 - 480	
Water connection		Garden Hose Connector	
Product code		4010.0017	4010.0018

